

# DIESEL BOWSER

**SP2400**



# DIESEL BOWSER

SPECIFICATION	SP-2400
Bowser capacity	2400 Litre
No. Compartments	3 Nos. (800 litre each)
Delivery	3 Valves with Separate pipe lines
Dispensing unit	Neogi
Flow Rate	30 - 90 LPM
Operating Temperature	- 5° C to 60° C
Electrical System	12V DC
Least count	10 ml
Display	6 Digit backlit LCD
Preset facility	Both litre and Rupees

## WHAT WE OFFER

- 📄 Elliptical Tank with 4mm Thick (IS 2062 Grade A) Sheet
- 📄 Mounting with chassis main frame with U-bolt and cleat plate
- 📄 Level Indicator - Aluminium Dip Stick
- 📄 Hose Reel – Highly Robust spring type self-retractable hose reel with hose
- 📄 Safety features – All standard fittings as per PESO standards with additional features complying to R.T.O norms
- 📄 Auto Shut – off nozzle.

## SILENT FEATURES

- 📄 Low cost of operation and maintenance in the long run
- 📄 Robust tank built quality
- 📄 High resistance to corrosion
- 📄 Thermal shock resistance
- 📄 Eliminate fuel pilferage
- 📄 Enhance fuel utilization

## Dispensing Unit



 **SPICON**

World of Solutions...

 Plot No. 10, 1st Floor, Park Avenue Colony, Ameerpet, Hyderabad, Telangana, India – 500016

 [infospicon@gmail.com](mailto:infospicon@gmail.com), [info@spicon.in](mailto:info@spicon.in),  [www.spicon.in](http://www.spicon.in)

 +91-4048554604